

Specification options

SYSTEM POWER

15W
21W

COLOUR TEMPERATURE

2700K
3000K
4000K

COLOUR RENDERING INDEX

CRI 90

ELECTRICAL

Non-Dim
phase DIM
1-10V
DALI

TRIM



Standard



TRIMLESS



TL Version

ILD-PRO100-WW

3000K
(Standard)




Light distribution for 3000K

13W 480lm-520lm



ILD-PRO100-WW-13W-930
ILD-PRO100-WW-13W-940



Specification Information


ILD-PRO100-WW 13W 480-520 lm

ILD-PRO-WALLWASHER	LED Output	Module Output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT
ILD-PRO100-WW-13W-930	1300lm	480lm	36V	350mA	13W	15W	90	3000K
ILD-PRO100-WW-13W-940	1400lm	520lm	36V	350mA	13W	15W	90	4000K

18W 650lm-700lm



ILD-PRO100-WW-18W-930
ILD-PRO100-WW-18W-940



Specification Information

ILD-PRO100-WW 18W 650-700 lm

ILD-PRO-WALLWASHER	LED Output	Module Output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT
ILD-PRO100-WW-18W-930	1700lm	650lm	36V	500mA	18W	21W	90	3000K
ILD-PRO100-WW-18W-940	1800lm	700lm	36V	500mA	18W	21W	90	4000K