

Specification options

SYSTEM POWER

21W
28W

COLOUR TEMPERATURE

2700K
3000K
4000K

COLOUR RENDERING INDEX

CRI 90

ELECTRICAL

Non-Dim
phase DIM
1-10V
DALI

TRIM



Standard



TRIMLESS



TL Version

ILD-PRO125-WW

3000K
(Standard)




Light distribution for 3000K

18W 750lm-800lm



ILD-PRO125-WW-18W-930
ILD-PRO125-WW-18W-940



Specification Information


ILD-PRO125-WW 18W 750-800 lm

ILD-PRO-WALLWASHER	LED Output	Module Output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT
ILD-PRO125-WW-18W-930	2000lm	750lm	36V	500mA	18W	21W	90	3000K
ILD-PRO125-WW-18W-940	2100lm	800lm	36V	500mA	18W	21W	90	4000K

25W 1000lm-1100lm



ILD-PRO125-WW-25W-930
ILD-PRO125-WW-25W-940



Specification Information

ILD-PRO125-WW 25W 1000-1100 lm

ILD-PRO-WALLWASHER	LED Output	Module Output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT
ILD-PRO125-WW-25W-930	2600lm	1000lm	36V	700mA	25W	28W	90	3000K
ILD-PRO125-WW-25W-940	2700lm	1100lm	36V	700mA	25W	28W	90	4000K