

Specification options

SYSTEM POWER

28W  
42W

COLOUR TEMPERATURE

2700K  
3000K  
4000K

COLOUR RENDERING INDEX

CRI 90

ELECTRICAL

Non-Dim  
phase DIM  
1-10V  
DALI

TRIM



Standard



TRIMLESS



TL Version

ILD-PRO150-WW

3000K  
(Standard)




Light distribution for 3000K

25W 1000lm-1100lm



ILD-PRO150-WW-25W-930  
ILD-PRO150-WW-25W-940



Specification Information


ILD-PRO150-WW 25W 1000-1100 lm

ILD-PRO-WALLWASHER	LED Output	Module Output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT
ILD-PRO150-WW-25W-930	2700lm	1000lm	36V	700mA	25W	28W	90	3000K
ILD-PRO150-WW-25W-940	2800lm	1100lm	36V	700mA	25W	28W	90	4000K

38W 1400lm-1500lm



ILD-PRO150-WW-38W-930  
ILD-PRO150-WW-38W-940



Specification Information

ILD-PRO150-WW 38W 1400-1500 lm

ILD-PRO-WALLWASHER	LED Output	Module Output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT
ILD-PRO150-WW-38W-930	3700lm	1400lm	36V	1050mA	38W	42W	90	3000K
ILD-PRO150-WW-38W-940	3900lm	1500lm	36V	1050mA	38W	42W	90	4000K