

Order options

SYSTEM POWER

28W  
42W  
56W

COLOUR TEMPERATURE

3000K  
4000K


COLOUR RENDERING INDEX

CRI 80  
CRI 90

ELECTRICAL

Non-Dim  
Phase Dim  
1-10V  
DALI Dim

LENS





18° Beam    30° Beam    60° Beam

REFLECTOR



Matt    White    Black

ILD200




Light distribution for 3000K


25W 2800 lm – 3400 lm




ILD200-25W-830-18  
ILD200-25W-840-18



ILD200-25W-830-30  
ILD200-25W-840-30



ILD200-25W-830-60  
ILD200-25W-840-60



Specification Details


ILD200-25W 2800-3400 Lm (CITIZEN LED)

Code	LED output	Module output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT	BEAM
ILD200-25W-830-18	3900 lm	3200 lm	36 V	700 mA	25 W	28 W	80	3000K	18°
ILD200-25W-840-18	4100 lm	3400 lm	36 V	700 mA	25 W	28 W	80	4000K	18°
ILD200-25W-830-30	3900 lm	3200 lm	36 V	700 mA	25 W	28 W	80	3000K	30°
ILD200-25W-840-30	4100 lm	3400 lm	36 V	700 mA	25 W	28 W	80	4000K	30°
ILD200-25W-830-60	3900 lm	2800 lm	36 V	700 mA	25 W	28 W	80	3000K	60°
ILD200-25W-840-60	4100 lm	3000 lm	36 V	700 mA	25 W	28 W	80	4000K	60°


38W 3900 lm – 4600 lm




ILD200-38W-830-18  
ILD200-38W-840-18



ILD200-38W-830-30  
ILD200-38W-840-30



ILD200-38W-830-60  
ILD200-38W-840-60



Specification Details

ILD200-38W 3900-4600 Lm (CITIZEN LED)

Code	LED output	Module output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT	BEAM
ILD200-38W-830-18	5400 lm	4400 lm	36 V	1050 mA	38 W	42 W	80	3000K	18°
ILD200-38W-840-18	5600 lm	4600 lm	36 V	1050 mA	38 W	42 W	80	4000K	18°
ILD200-38W-830-30	5400 lm	4400 lm	36 V	1050 mA	38 W	42 W	80	3000K	30°
ILD200-38W-840-30	5600 lm	4600 lm	36 V	1050 mA	38 W	42 W	80	4000K	30°
ILD200-38W-830-60	5400 lm	3900 lm	36 V	1050 mA	38 W	42 W	80	3000K	60°
ILD200-38W-840-60	5600 lm	4100 lm	36 V	1050 mA	38 W	42 W	80	4000K	60°

Order options

SYSTEM POWER

28W  
42W  
56W

COLOUR TEMPERATURE

3000K  
4000K


COLOUR RENDERING INDEX

CRI 80  
CRI 90

ELECTRICAL

Non-Dim  
Phase Dim  
1-10V  
DALI Dim

LENS



18° Beam    30° Beam    60° Beam

REFLECTOR




Matt    White    Black


52W    4800 lm-5600 lm




ILD200-52W-830-18  
ILD200-52W-840-18



ILD200-52W-830-30  
ILD200-52W-840-30



ILD200-52W-830-60  
ILD200-52W-840-60



Specification Details

ILD200-52W 4800-5600 Lm ( CITIZEN LED )

Code	LED output	Module output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT	BEAM
ILD200-52W-830-18	6600 lm	5400 lm	36 V	1400 mA	52 W	56 W	80	3000K	18°
ILD200-52W-840-18	6800 lm	5600 lm	36 V	1400 mA	52 W	56 W	80	4000K	18°
ILD200-52W-830-30	6600 lm	5400 lm	36 V	1400 mA	52 W	56 W	80	3000K	30°
ILD200-52W-840-30	6800 lm	5600 lm	36 V	1400 mA	52 W	56 W	80	4000K	30°
ILD200-52W-830-60	6600 lm	4800 lm	36 V	1400 mA	52 W	56 W	80	3000K	60°
ILD200-52W-840-60	6800 lm	5000 lm	36 V	1400 mA	52 W	56 W	80	4000K	60°