

Order options

SYSTEM POWER

9W
13W

COLOUR TEMPERATURE

3000K
4000K

COLOUR RENDERING INDEX

CRI 80
CRI 90

ELECTRICAL

Non-Dim
Phase Dim
1-10V
DALI

LENS



25° Beam

50° Beam

REFLECTOR




Matt

White


Black

ILD75

3000K
(Standard)



IP54 UGR <19




Light distribution for 3000K

7.5W 700 lm – 750 lm



ILD75-7.5W-830-25
ILD75-7.5W-840-25




Diameter (cm)	Height, Emax
Ø39	1m 3318lx
Ø78	2m 828lx
Ø117	3m 368lx
Ø156	4m 207lx
Ø195	5m 131lx

20° 10° 0° 10° 20°



ILD75-7.5W-830-50
ILD75-7.5W-840-50



Diameter (cm)	Height, Emax
Ø96	1m 1012lx
Ø192	2m 253lx
Ø288	3m 112lx
Ø385	4m 64lx
Ø481	5m 41lx

20° 10° 0° 10° 20°

Specification Details


ILD75-7.5W 700-750 Lm (CITIZEN LED)

Code	LED output	Module output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT	BEAM
ILD75-7.5W-830-25	1000 lm	700 lm	31 V	250 mA	7.5 W	9 W	80	3000K	25°
ILD75-7.5W-840-25	1100 lm	750 lm	31 V	250 mA	7.5 W	9 W	80	4000K	25°
ILD75-7.5W-830-50	1000 lm	700 lm	31 V	250 mA	7.5 W	9 W	80	3000K	50°
ILD75-7.5W-840-50	1100 lm	750 lm	31 V	250 mA	7.5 W	9 W	80	4000K	50°

11W 900 lm – 950 lm



ILD75-11W-830-25
ILD75-11W-830-25




Diameter (cm)	Height, Emax
Ø39	1m 4407lx
Ø78	2m 1101lx
Ø116	3m 489lx
Ø155	4m 275lx
Ø194	5m 176lx

20° 10° 0° 10° 20°



ILD75-11W-830-50
ILD75-11W-830-50



Diameter (cm)	Height, Emax
Ø98	1m 1379lx
Ø197	2m 344lx
Ø296	3m 152lx
Ø395	4m 85lx
Ø494	5m 54lx

20° 10° 0° 10° 20°

Specification Details

ILD75-11W 900-950 Lm (CITIZEN LED)

Code	LED output	Module output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT	BEAM
ILD75-11W-830-25	1300 lm	900 lm	31 V	350 mA	11 W	13 W	80	3000K	25°
ILD75-11W-840-25	1400 lm	950 lm	31 V	350 mA	11 W	13 W	80	4000K	25°
ILD75-11W-830-50	1300 lm	900 lm	31 V	350 mA	11 W	13 W	80	3000K	50°
ILD75-11W-840-50	1400 lm	950 lm	31 V	350 mA	11 W	13 W	80	4000K	50°