

Specification options

**SYSTEM POWER**

15W  
21W

**COLOUR TEMPERATURE**

2700K  
3000K  
4000K

**COLOUR RENDERING INDEX**

CRI 90

**ELECTRICAL**

Non-Dim  
phase DIM  
1-10V  
DALI

**PRIMARY REFLECTOR**



28° Beam 35° Beam



50° Beam

**TRIM**



Standard

**TRIMLESS**



TL Version

**SECONDARY REFLECTOR**



Specular Black White



Matt




**ILDSQ-PRO100F**



96x96



104x104




Light distribution for 3000K


**13W 900lm-950lm**




ILDSQ-PRO100-F-13W-930-28  
ILDSQ-PRO100-F-13W-940-28



ILDSQ-PRO100-F-13W-930-35  
ILDSQ-PRO100-F-13W-940-35



ILDSQ-PRO100-F-13W-930-50  
ILDSQ-PRO100-F-13W-940-50



Specification Information


**ILDSQ-PRO100F 13W 900-950 lm**

ILDSQ-PRO-FIXED	LED Output	Module Output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT	BEAM
ILDSQ-PRO100-F-13W-930-28	1300lm	900lm	36V	350mA	13W	15W	90	3000K	28°
ILDSQ-PRO100-F-13W-940-28	1400lm	950lm	36V	350mA	13W	15W	90	4000K	28°
ILDSQ-PRO100-F-13W-930-35	1300lm	900lm	36V	350mA	13W	15W	90	3000K	35°
ILDSQ-PRO100-F-13W-940-35	1400lm	950lm	36V	350mA	13W	15W	90	4000K	35°
ILDSQ-PRO100-F-13W-930-50	1300lm	900lm	36V	350mA	13W	15W	90	3000K	50°
ILDSQ-PRO100-F-13W-940-50	1400lm	950lm	36V	350mA	13W	15W	90	4000K	50°


**18W 1200lm-1300lm**




ILDSQ-PRO100-F-18W-930-28  
ILDSQ-PRO100-F-18W-940-28



ILDSQ-PRO100-F-18W-930-35  
ILDSQ-PRO100-F-18W-940-35



ILDSQ-PRO100-F-18W-930-50  
ILDSQ-PRO100-F-18W-940-50



Specification Information

**ILDSQ-PRO100F 18W 1200-1300 lm**

ILDSQ-PRO-FIXED	LED Output	Module Output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT	BEAM
ILDSQ-PRO100-F-18W-930-28	1700lm	1200lm	36V	500mA	18W	21W	90	3000K	28°
ILDSQ-PRO100-F-18W-940-28	1800lm	1300lm	36V	500mA	18W	21W	90	4000K	28°
ILDSQ-PRO100-F-18W-930-35	1700lm	1200lm	36V	500mA	18W	21W	90	3000K	35°
ILDSQ-PRO100-F-18W-940-35	1800lm	1300lm	36V	500mA	18W	21W	90	4000K	35°
ILDSQ-PRO100-F-18W-930-50	1700lm	1200lm	36V	500mA	18W	21W	90	3000K	50°
ILDSQ-PRO100-F-18W-940-50	1800lm	1300lm	36V	500mA	18W	21W	90	4000K	50°