

Specification options

SYSTEM POWER

21W
48W

COLOUR TEMPERATURE

2700K
3000K
4000K

COLOUR RENDERING INDEX

CRI 90

ELECTRICAL

Non-DIM
phase DIM
1-10V
DALI

PRIMARY REFLECTOR



TRIM



TRIMLESS




ANTI-GLARE ACCESSORY



SECONDARY REFLECTOR



Specular






ILDSQ-PRO125A

3000K
(Standard)

122x122



130x130




Light distribution for 3000K


18W 1300lm - 1400lm




ILDSQ-PRO125-A-18W-930-20
ILDSQ-PRO125-A-18W-940-20



ILDSQ-PRO125-A-18W-930-40
ILDSQ-PRO125-A-18W-940-40



ILDSQ-PRO125-A-18W-930-50
ILDSQ-PRO125-A-18W-940-50



Specification Information


ILDSQ-PRO125A 18W 1300-1400 lm

ILDSQ-PRO-ADJUSTABLE	LED Output	Module Output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT	BEAM
ILDSQ-PRO125-A-18W-930-20	2000lm	1300lm	36V	500mA	18W	21W	90	3000K	20°
ILDSQ-PRO125-A-18W-940-20	2100lm	1400lm	36V	500mA	18W	21W	90	4000K	20°
ILDSQ-PRO125-A-18W-930-40	2000lm	1300lm	36V	500mA	18W	21W	90	3000K	40°
ILDSQ-PRO125-A-18W-940-40	2100lm	1400lm	36V	500mA	18W	21W	90	4000K	40°
ILDSQ-PRO125-A-18W-930-50	2000lm	1300lm	36V	500mA	18W	21W	90	3000K	50°
ILDSQ-PRO125-A-18W-940-50	2100lm	1400lm	36V	500mA	18W	21W	90	4000K	50°


25W 1700lm - 1800lm




ILDSQ-PRO125-A-25W-930-20
ILDSQ-PRO125-A-25W-940-20



ILDSQ-PRO125-A-25W-930-40
ILDSQ-PRO125-A-25W-940-40



ILDSQ-PRO125-A-25W-930-50
ILDSQ-PRO125-A-25W-940-50



Specification Information

ILDSQ-PRO125A 25W 1700-1800 lm

ILDSQ-PRO-ADJUSTABLE	LED Output	Module Output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT	BEAM
ILDSQ-PRO125-A-25W-930-20	2600lm	1700lm	36V	700mA	25W	28W	90	3000K	20°
ILDSQ-PRO125-A-25W-940-20	2700lm	1800lm	36V	700mA	25W	28W	90	4000K	20°
ILDSQ-PRO125-A-25W-930-40	2600lm	1700lm	36V	700mA	25W	28W	90	3000K	40°
ILDSQ-PRO125-A-25W-940-40	2700lm	1800lm	36V	700mA	25W	28W	90	4000K	40°
ILDSQ-PRO125-A-25W-930-50	2600lm	1700lm	36V	700mA	25W	28W	90	3000K	50°
ILDSQ-PRO125-A-25W-940-50	2700lm	1800lm	36V	700mA	25W	28W	90	4000K	50°