

Specification options

SYSTEM POWER

28W
42W

COLOUR TEMPERATURE

2700K
3000K
4000K

COLOUR RENDERING INDEX

CRI 90

ELECTRICAL

Non-Dim
phase DIM
1-10V
DALI

TRIM




Standard

TRIMLESS






TL Version

ILDSQ-PRO150-WW




3000K
(Standard)



Light distribution for 3000K

25W 900lm-950lm

ILDSQ-PRO150-WW-25W-930
ILDSQ-PRO150-WW-25W-940




Specification Information

ILDSQ-PRO150-WW 25W 900-950 lm

ILDSQ-PRO-WALLWASHER	LED Output	Module Output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT
ILDSQ-PRO150-WW-25W-930	2700lm	900lm	36V	700mA	25W	28W	90	3000K
ILDSQ-PRO150-WW-25W-940	2800lm	950lm	36V	700mA	25W	28W	90	4000K

38W 1300lm-1400lm

ILDSQ-PRO150-WW-38W-930
ILDSQ-PRO150-WW-38W-940



Specification Information

ILDSQ-PRO150-WW 38W 1300-1400 lm

ILDSQ-PRO-WALLWASHER	LED Output	Module Output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT
ILDSQ-PRO150-WW-38W-930	3700lm	1300lm	36V	1050mA	38W	42W	90	3000K
ILDSQ-PRO150-WW-38W-940	3900lm	1400lm	36V	1050mA	38W	42W	90	4000K