

Order options

SYSTEM POWER

9W  
13W

COLOUR TEMPERATURE

3000K  
4000K

COLOUR RENDERING INDEX

CRI180  
CRI190

ELECTRICAL

Non-Dim  
Phase Dim  
1-10V  
DALI

LENS



25° Beam      60° Beam


REFLECTOR




Matt      White      Black

ILDSQ65

3000K  
(Standard)



IP54    UGR <19




Light distribution for 3000K

7.5W    700 lm – 750 lm



ILDSQ65-7.5W-830-25  
ILDSQ65-7.5W-840-25




Diameter (cm)	Height, Emax
Ø40	1m 248lx
Ø81	2m 622lx
Ø121	3m 276lx
Ø161	4m 155lx
Ø201	5m 99lx

20° 10° 0° 10° 20°



ILDSQ65-7.5W-830-60  
ILDSQ65-7.5W-840-60



Diameter (cm)	Height, Emax
Ø118	1m 650lx
Ø235	2m 162lx
Ø353	3m 72lx
Ø471	4m 41lx
Ø589	5m 26lx

20° 10° 0° 10° 20°

Specification Details


ILDSQ65-7.5W 700-750 Lm ( CITIZEN LED )

Code	LED output	Module output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT	BEAM
ILDSQ65-7.5W-830-25	1000 lm	700 lm	31 V	250 mA	7.5 W	9 W	80	3000K	25°
ILDSQ65-7.5W-840-25	1100 lm	750 lm	31 V	250 mA	7.5 W	9 W	80	4000K	25°
ILDSQ65-7.5W-830-60	1000 lm	700 lm	31 V	250 mA	7.5 W	9 W	80	3000K	60°
DS65-7.5W-840-60	1100 lm	750 lm	31 V	250 mA	7.5 W	9 W	80	4000K	60°

11W    900 lm – 950 lm



ILDSQ65-11W-830-25  
ILDSQ65-11W-840-25




Diameter (cm)	Height, Emax
Ø40	1m 3141lx
Ø80	2m 785lx
Ø120	3m 349lx
Ø159	4m 196lx
Ø199	5m 125lx

20° 10° 0° 10° 20°



ILDSQ65-11W-830-60  
ILDSQ65-11W-840-60



Diameter (cm)	Height, Emax
Ø123	1m 820lx
Ø247	2m 205lx
Ø371	3m 91lx
Ø495	4m 51lx
Ø619	5m 33lx

20° 10° 0° 10° 20°

Specification Details

DS65-11W 900-950 Lm ( CITIZEN LED )

Code	LED output	Module output	LED Voltage	LED Current	LED Power	System Power	CRI	CCT	BEAM
ILDSQ65-11W-830-25	1300 lm	900 lm	31 V	350 mA	11 W	13 W	80	3000K	25°
ILDSQ65-11W-840-25	1400 lm	950 lm	31 V	350 mA	11 W	13 W	80	4000K	25°
ILDSQ65-11W-830-60	1300 lm	900 lm	31 V	350 mA	11 W	13 W	80	3000K	60°
ILDSQ65-11W-840-60	1400 lm	950 lm	31 V	350 mA	11 W	13 W	80	4000K	60°