



SPECIFICATIONS OVERVIEW:

Version	Adjustable
Trim Finish	White, Black
Reflector	Matt Silver, White, Black
Colour Temperature	3000K, 4000K (others on request)
Beam Angle	18°, 24°, 35°, 50°
LED Power	4W
LED	CRI >90, L80 B10/50,000hr, <3SDCM
Controls	Non-Dim, Phase Dim, 1-10V, DALI
COI	Compliant (4000K only)
IP Rating	IP20
Warranty	5 Years



SPECIFICATIONS CODES:

ILD-PRO45A-4W 350-380 lm nominal

CODE	LED Output	Module Output	LED Voltage	LED Current	LED Power	CRI	CCT	BEAM
ILD-PRO45A-4W-930-18	500lm	350lm	12V	350mA	4W	90	3000K	18°
ILD-PRO45A-4W-940-18	550lm	380lm	12V	350mA	4W	90	4000K	18°
ILD-PRO45A-4W-930-24	500lm	350lm	12V	350mA	4W	90	3000K	24°
ILD-PRO45A-4W-940-24	550lm	380lm	12V	350mA	4W	90	4000K	24°
ILD-PRO45A-4W-930-35	500lm	350lm	12V	350mA	4W	90	3000K	35°
ILD-PRO45A-4W-940-35	550lm	380lm	12V	350mA	4W	90	4000K	35°
ILD-PRO45A-4W-930-50	500lm	350lm	12V	350mA	4W	90	3000K	50°
ILD-PRO45A-4W-940-50	550lm	380lm	12V	350mA	4W	90	4000K	50°