


SPECIFICATIONS OVERVIEW:

Version	Fixed
Trim Finish	White, Black
Reflector	Matt Silver, White, Black
Colour Temperature	3000K, 4000K (others on request)
Beam Angle	30°, 50°
LED Power	9W, 13W
LED	CRI >90, L80 B10/50,000hr, <3SDCM
Controls	Non-Dim, Phase Dim, 1-10V, DALI
COI	Compliant (4000K only)
IP Rating	IP54
Warranty	5 Years



SPECIFICATIONS CODES:

ILD100-9W 850-1000 Lm nominal (CITIZEN LED)

Code	LED output	Module output	LED Voltage	LED Current	LED Power	CRI	CCT	BEAM
ILD100-9W-930-30	1100 lm	950 lm	36 V	250 mA	9W	>90	3000K	30°
ILD100-9W-940-30	1200 lm	1000 lm	36 V	250 mA	9W	>90	4000K	30°
ILD100-9W-930-50	1100 lm	850 lm	36 V	250 mA	9W	>90	3000K	50°
ILD100-9W-940-50	1200 lm	900 lm	36 V	250 mA	9W	>90	4000K	50°

ILD100-13W 1100-1400 Lm nominal (CITIZEN LED)

Code	LED output	Module output	LED Voltage	LED Current	LED Power	CRI	CCT	BEAM
ILD100-13W-930-30	1500 lm	1300 lm	36 V	350 mA	13W	>90	3000K	30°
ILD100-13W-940-30	1600 lm	1400 lm	36 V	350 mA	13W	>90	4000K	30°
ILD100-13W-930-50	1500 lm	1100 lm	36 V	350 mA	13W	>90	3000K	50°
ILD100-13W-940-50	1600 lm	1200 lm	36 V	350 mA	13W	>90	4000K	50°