


### SPECIFICATIONS OVERVIEW:

Version	Fixed
Trim Finish	White, Black
Reflector	Matt Silver, White, Black
Colour Temperature	3000K, 4000K (others on request)
Beam Angle	25°, 60°
LED Power	7.5W, 11W
LED	CRI >90, L80 B10/50,000hr, <3SDCM
Controls	Non-Dim, Phase Dim, 1-10V, DALI
IP Rating	IP54
Warranty	5 Years



### SPECIFICATIONS CODES:

ILDSQ65-7.5W 600-650 Lm nominal (CITIZEN LED)

Code	LED output	Module output	LED Voltage	LED Current	LED Power	CRI	CCT	BEAM
ILD75-7.5W-930-25	900 lm	600 lm	31 V	250 mA	7.5W	>90	3000K	25°
ILD75-7.5W-940-25	950 lm	650 lm	31 V	250 mA	7.5W	>90	4000K	25°
ILD75-7.5W-930-60	900 lm	600 lm	31 V	250 mA	7.5W	>90	3000K	60°
ILD75-7.5W-940-60	950 lm	650 lm	31 V	250 mA	7.5W	>90	4000K	60°

ILDSQ65-11W 800-850 Lm nominal (CITIZEN LED)

Code	LED output	Module output	LED Voltage	LED Current	LED Power	CRI	CCT	BEAM
ILD75-11W-930-25	1200 lm	800 lm	31 V	350 mA	11W	>90	3000K	25°
ILD75-11W-940-25	1300 lm	850 lm	31 V	350 mA	11W	>90	4000K	25°
ILD75-11W-930-60	1200 lm	800 lm	31 V	350 mA	11W	>90	3000K	60°
ILD75-11W-940-60	1300 lm	850 lm	31 V	350 mA	11W	>90	4000K	60°